

USABlueBook® Standard Submersible Level Transmitters Order Form

Every Transmitter Features:

- Slim design with bullet-nose nose cap
- Vented to compensate for changes in barometric pressure
- Maintenance-free vent filter
- Lightning surge protected*

*Surge protection is not guaranteed and is not covered by warranty. We recommend Surge Protection Module 17701 for additional protection.

Wetted materials:	316 SS body, PVC nose cap, Buna-N seals (cable options below)
Accuracy:	±0.25% of full scale
Power:	13-30 VDC
Output:	4-20 mA, 2-wire
Pressure limit:	2x full scale
Temperature range:	0 to 140°F (compensated)
Dimensions:	7.2"L x 1.0"Dia
Rating:	CE

Potable water/
down well



Choose from ready-to-order or custom-configured transmitters

Ready-to-Order Transmitters

Below is our ready-to-order selection. Please review before requesting a custom configuration—we may already have what you need.

RANGE (PSI)	RANGE (FT H ₂ O)	CABLE LENGTH	CABLE MATERIAL	STOCK #
0 to 5	0 to 11.55	40'	Polyurethane	73730
0 to 10	0 to 23.10	40'	Polyurethane	73731
0 to 15	0 to 34.65	60'	Polyurethane	73732
0 to 20	0 to 46.20	60'	Polyurethane	73733
0 to 30	0 to 69.30	90'	Polyurethane	73734

Surge Protection Module [17701](#)

Custom-Configured Transmitters

Custom transmitters have the standard features and specifications shown at the top of this page, but offer you flexibility to change certain specifications and delivery options. Most custom models are built in 2 to 3 weeks. Quick-ship option available (5-day build time).

→ **To begin your quote:** Call **800.548.1234** with your requirements (available options listed below), or complete this form and email it to customerservice@usabluebook.com or fax it to **847.689.3030**. We will contact you with pricing and delivery times for your approval.

Please indicate your requirements for each of the following:

Cable Material (check one): ETFE Polyurethane

Maximum Range Value in psi (up to 400 psi in 0.01 increments): _____ psi

Cable Length (10 to 2000 feet): _____ feet

Inline Threaded Process Connection (1/4" MNPT): Yes No (comes with standard plastic nose cap)

Include Surge Protection Module (Stock # 17701): Yes No

Quantity _____

Quick Ship (5 business day build time; extra fee per unit applies): Yes No

Contact Information

Name _____

Company _____

Customer/Account # (if known) _____

Email _____

Phone Number _____