

MAINTENANCE Oils, Greases, Lubricants & Adhesives

RTV Silicone Sealants

- Excellent adhesion to a variety of surfaces
- Withstands temperatures up to 650°F
- Available in blue, white or hi-temp red

RTV silicone sealants are useful in a wide range of applications around the plant. Their excellent adhesive properties make them ideal for a variety of surfaces including clean metal, glass, most types of wood, ceramic, natural and synthetic fiber and many painted and plastic surfaces. Available in 10.3-oz cartridges or 8-oz aerosol cans.

Solution 450 RTV withstands temperatures up to 450°F. Ideal for most formed-in-place gasket applications. Tack-free in about 18 minutes, with a full cure time of 24 hours. Choose from blue or white color.

Solution 600 High-Temperature RTV withstands temperatures up to 600°F continuous and 650°F intermittent. Ideal for gasket applications where the equipment runs very warm. Tack-free in less than 1 hour, with a full cure time of 5 to 7 days. Red color.



Agency approvals:

FDA-USDA approved.
Meets and exceeds Federal specification TT-S-0230C and TT-S-001543A (Com-NBS), ASTM C 920 Type S, MIL-A46106A Type 1.

DESCRIPTION	COLOR	STOCK #	EACH	QTY 12+
Solution 450 RTV Silicone Sealant	Blue	13923	\$	
Solution 450 RTV Silicone Sealant	White	13924		
Solution 600 Hi-Temp RTV Silicone Sealant	Red	13925		
Solution 450 RTV Silicone Aerosol	Blue	96910		
Solution 600 Hi-Temp RTV Silicone Aerosol	Red	96911		
Caulking Gun		78718		—

MRO Anaerobic Threadlockers

- Meets military specifications
- Economical
- Choose from medium- and high-strength formulations

Use MRO threadlockers on any fastener when you need a secure connection. One drop prevents loosening, even under vibration. Hardening begins in about 5 to 15 minutes, and full cure time is about 24 hours. Threadlockers also seal threads against leakage and prevent rust and corrosion. Temperature range is -65 to 300°F.

MRO Solution 10 is a medium strength, general-purpose threadlocker for stainless steel and most metal fasteners between 1/4" and 3/4" diameters. It is removable with hand tools. Fills spaces up to 0.01". Meets MIL-S-46163A Type II Grade N specifications.

MRO Solution 11 is a high-strength threadlocker for most metal fasteners up to 1" diameter. It is removable with heat and/or special tools. Fills spaces up to 0.008". Meets MIL-S-46163A Type I Grade K specifications.



DESCRIPTION	STOCK #	EACH
MRO Solution 10 Medium Strength Blue Threadlocker, 10 mL	14016	\$
MRO Solution 10 Medium Strength Blue Threadlocker, 50 mL	14017	
MRO Solution 11 High Strength Red Threadlocker, 10 mL	14018	
MRO Solution 11 High Strength Red Threadlocker, 50 mL	14019	

Loctite® 518 Flange Sealants

- Medium-strength
- General purpose gasketing

NEW!

This anaerobic gasketing material fills gaps up to 0.25 mm and forms a flexible, chemical-resistant seal that will not tear or decay. Applications include sealing close-fitting joints between rigid metal faces and flanges, or creating a formed-in-place gasket on rigid flanged connections.

Use on rigid iron, aluminum and steel flanged mating surfaces. Parts disassemble easily, even after extended service. Meets NSF/ANSI 61 Standards.



DESCRIPTION	STOCK #	EACH
Loctite Flange Sealant, 6 mL	330266	\$



Gorilla® Glue

- Choose from original or super glue gel formulas

Put Gorilla Glue to work on repair projects around the plant. Choose from two formulas. **Original Gorilla Glue** is ideal for almost any repair. Water activated, it expands into materials to form a strong bond to virtually anything. Glue dries in 1-2 hours with full cure after 24 hours. Can be sanded, painted or stained after application.



92665



92666

Gorilla Super Glue Gel is a high strength, no-run, quick-set glue—great for vertical applications. Rubber-toughened to prevent cracking under pressure, it bonds metal, wood, paper, ceramics, leather and most plastics. An anti-clog cap with metal pin ensures an airtight seal. Glue dries in seconds, with full cure in 24 hours.

DESCRIPTION	STOCK #	EACH
Original Gorilla Glue, 4 oz	92666	\$
Gorilla Super Glue Gel, 0.5 oz	92665	

Loctite® Super Glue

- Dries clear and sets quickly without clamping
- Choose from gel or liquid formulas

Loctite super glue features a pinpoint accuracy tip for precise bonding. It is resistant to moisture, freezing temperatures and many chemicals. Choose from two formulas.

Super Glue Gel Control™ is a non-drip formula that's great for porous surfaces and vertical applications.

Super Glue Liquid Professional is ideal for bonding non-porous smooth, close-fitting surfaces.



92663



92664

DESCRIPTION	STOCK #	EACH
Loctite Super Glue Gel Control, 0.14 oz	92663	\$
Loctite Super Glue Liquid Professional, 0.71 oz	92664	