

PIPE Gaskets & Flanges

Flanges

Cast-Iron Threaded Companion Flanges

Standard black finish

NPT THREAD	STOCK #	EACH
1 1/2"	13006	\$
2"	13000	
2 1/2"	13001	
3"	13002	
4"	13003	
6"	13004	
8"	13005	

Cast-Iron Reducing Companion Flanges

Standard black finish

SIZE, FLG x NPT	STOCK #	EACH
3" x 2"	17069	\$
4" x 2"	17070	
4" x 3"	17071	
5" x 4"	17072	
6" x 2"	17073	
6" x 3"	17074	
6" x 4"	17075	
6" x 5"	13007	
8" x 2"	17076	
8" x 3"	17077	
8" x 4"	17078	
8" x 6"	17079	

Schedule 80 PVC Socket Flanges

150# Class

PIPE SIZE	# OF BOLTS	STOCK #	EACH
1 1/2"	4	24634	\$
2"	4	45450	
2 1/2"	4	24633	
3"	4	45452	
4"	8	45454	
6"	8	45456	
8"	8	24635	

Schedule 80 PVC Blind Flanges

150# Class

PIPE SIZE	# OF BOLTS	STOCK #	EACH
1 1/2"	4	15202	\$
2"	4	15203	
2 1/2"	4	15204	
3"	4	15205	
4"	8	15206	
6"	8	15207	
8"	8	15208	

Cast-Iron Blind Flanges

150# Class

PIPE SIZE	# OF BOLTS	STOCK #	EACH
2"	4	27422	\$
2 1/2"	4	27423	
3"	4	27424	
4"	8	27425	
6"	8	27426	
8"	8	27427	

Mechanical Joint Accessory Kits

- Includes standard T-head bolts, transition gasket and ID gland



PIPE SIZE	DUCTILE IRON PIPE		IPS PIPE	
	STOCK #	EACH	STOCK #	EACH
3"	15271	\$	15277	\$
4"	15272		15278	
6"	15273		15279	
8"	15274		15280	
10"	15275		15281	
12"	15276		15282	

Gasket Materials

- Cut your own gaskets to any shape or size
- Wide variety of materials



Gasket materials are furnished in one square yard (36" x 36") sheet. Five different materials are available to suit a wide range of applications. Red rubber offers good abrasion resistance. Black neoprene is chemically resistant to silicone oil and grease. EPR offers good weather resistance, but is not recommended for use with oils or grease. Vegetable fiber has good flexibility and oil resistance. Viton® is the preferred material for maximum chemical resistance and high-temperature applications.

COMPOSITION	MAX TEMP	1/16" THICKNESS		1/8" THICKNESS	
		STOCK #	EACH	STOCK #	EACH
Red Rubber	158°F	16010	\$	16020	\$
Black Neoprene	230°F	16042		—	—
EPR	250°F	16011		16021	
Vegetable Fiber	250°F	16030		16040	
Viton	400°F	16041		—	—

Gasket Punches

Gasket holes are generally sized 1/8" larger in diameter than the bolt size. For example, select a 7/8" punch for flanges using 3/4" bolts. Set includes 1/4", 3/8", 1/2", 5/8", 3/4", 7/8" and 1".



16070

SIZE	STOCK #	EACH
5/8"	16070	\$
3/4"	16075	
7/8"	16080	
1"	16090	
Set of Seven	16076	

Gasket and Washer Cutters

Designed for cutting gaskets and washers any size up to and including 24" OD. Can be used with bit brace, drill press or by hand. Blades included. Replaceable blades are packed two per set.



DESCRIPTION	STOCK #	EACH
Gasket Cutter	16050	\$
Extra Blade Set	16060	

BEST!
SELLER

Flange Packs

Full face 1/8" red rubber gasket with zinc-plated or SS bolts sized for standard 125/150 lb flanges.



PIPE SIZE	# OF BOLTS	ZINC PLATED			STAINLESS STEEL		
		STOCK #	EACH	QTY 5+	STOCK #	EACH	QTY 5+
2"	4	16658	\$	\$	16656	\$	\$
2 1/2"	4	16659			16673		
3"	4	16660			16675		
4"	8	16661			16677		
6"	8	16662			16679		
8"	8	16663			16681		
10"	12	16687			16683		
12"	12	16689			16685		