

Product SPOTLIGHT

BW™ Max XT II Four-Gas Detectors

- New name—same great product
- Download up to 30 recent alarm events with the optional IR connectivity kit
- Full 2-year warranty including sensors

The Max XT II delivers high-performance detection of H₂S, CO, O₂ and combustible gases (LEL). It features a powerful internal pump for remote sampling, making it perfect for confined space applications. This rugged, lightweight unit has an impact- and water-resistant housing, and a large LCD screen. One-button operation is easy, whether it's in your hand or attached to your belt.

IntelliFlash verifies operation and compliance to both the user and supervisors from up to 20 feet away. The unit's triple-alarm system activates audible, visual and vibrating alarms in the event of low, high, TWA or STEL alarm conditions. The detector stores the 30 most recent alarm events, and can hold six hours to five years of data depending on interval settings.

Upon start-up, the unit's self-test checks its battery, pump, sensors, circuitry and alarms, and advises when the next calibration is due. The detector is powered by a lithium polymer battery pack. Typical runtime for normal operation is 13 hours. Recharge time is typically no more than 6 hours.

An optional IR connectivity kit (stock # 72497) lets you access and download data, as well as change your user-adjustable settings. This kit includes the Fleet Manager Software CD, connector and cable. Gas detectors are compatible with the IntelliDoX docking station (stock # 331997; see page 1439) for convenient calibration, test and record storage.

Includes: lithium polymer rechargeable battery, charging adapter, SS alligator belt clip, 3' calibration tubing w/ quick-connect fitting, 10'L sampling tubing, five pump filters, instructions and quick-reference card.

Note: For a complete system, order the Max XT II gas detector, calibration gas, regulator and hard-shell Pelican case. The optional protective black rubber boot and IR connectivity kit for downloading data are sold separately.

DESCRIPTION	STOCK #	EACH
Max XT II Gas Detector	72491	\$

REPLACEMENT SENSORS

O ₂ Sensor (Max XT II Only)	72498	\$
LEL Sensor	72493	
CO Sensor	72494	
H ₂ S Sensor	72495	

CALIBRATION SUPPLIES

Calibration Gas, 58-Liter Cylinder	55818	\$
Regulator, 0.5 LPM	71674	
IR Connectivity Kit	72497	
IntelliDoX Docking Station	331997	
Demand Flow Regulator (use with IntelliDoX Station)	71679	

SAMPLING PROBES & ACCESSORIES: Sampling probes let you sample hard-to-reach places. Collapsible sampling probe (stock # 330658) extends to 6'L, and folds to a compact size.

12"L Sample Probe	97064	\$
6'L Collapsible Probe	330658	
Syringe Filter Replacement for 12"L Sample Probe	330659	
Sample Probe Filter and Gasket Replacement for 12"L Sample Probe	330660	
Particulate Filter Replacement for 12"L Sample Probe, Pack of 25	330661	

SAMPLING HOSE & ACCESSORIES: sampling hose include 3 metallic sintered particulate filters.

Replacement 10'L Sampling Hose	97065	\$
20'L Sampling Hose	97066	
65'L Sampling Hose	330219	
75'L Sampling Hose	97067	
Replacement Metallic Sintered Particulate Filter	330218	
Quick-Connect Fitting Spares for Hose, Pack of 2	97071	
Water Sampling Float	330662	

GENERAL ACCESSORIES

Replacement Particulate Pump Filter, Pack of 5	97070	\$
Replacement Hydrophobic Pump Filters, Pack of 5	97069	
Waterproof Hard-Shell Pelican Case	42700	
Rubber Boot, Black	72496	
Replacement Power Adapter	31776	
Vehicle Power Adapter	214482	

High performance at an affordable price!

Honeywell
THE POWER OF CONNECTED



Shown with optional boot (72496)



Gases detected

- Oxygen (O₂):** 0 to 30% by volume
- Combustible (LEL):** 0 to 100%
- Carbon monoxide (CO):** 0 to 1000 ppm
- Hydrogen sulfide (H₂S):** 0 to 200 ppm

Alarms

- Audible:** 95 dBA at 1 ft
- Visual:** three flashing alarm bars
- Vibration:** pulses warning in gas alarm

Operating conditions:

- 4 to 122°F (-20 to 50°C);
- 10 to 100% RH (non-condensing)

IP rating:

- instrument IP66/67

Battery

- Battery life:** 13 hours
- Charge time:** less than 6 hours

Dimensions:

- 2.8"W x 5.1"H x 2.0"D

Weight:

- 11.1 oz (316 g)

Compliance:

- approved by CSA to U.S. and Canadian standards; CAN/CSA C22.2 No. 157
- Class 1, Division 1, Groups A, B, C and D;
- ATEX certified; CE marked



Automate calibration and bump testing with the **BW IntelliDoX Docking Station.** See page 1439 for details.