

# Spanco® Portable Gantry Cranes

- Under 3 minutes to assemble and disassemble!
- 10-year warranty on manual systems
- Meets or exceeds standards set by CMAA and OSHA

Lift and move pumps, valves or blowers anywhere in your plant with Spanco's portable aluminum and T-Series gantry cranes.

**Note:** These gantry cranes are strictly equipment-rated and are not to be used for lifting, supporting or transporting personnel.

## Aluminum Gantry Cranes

- Extremely stable under heavy weight-bearing loads

Starting as light as 116 pounds, these cranes are ideal for operators who need fast lift relocation from site to site. Designed to easily fit in most service trucks, they're portable enough to go virtually anywhere. One person can quickly assemble and disassemble the crane in under three minutes.

Height under I-beam measures up to 12'2" and locks into place via a spring-loaded steel pin. Poly caster wheels with brakes make transporting your crane around the jobsite even easier.

Enhance your aluminum gantry crane with optional accessories. **Height extensions** provide two feet of additional crane height. **Pneumatic tires** (available with or without brakes) are ideal for soft terrain and outdoor jobsites.

**Shipping:** All cranes ship motor freight.



### Aluminum Gantry Cranes

MAX WEIGHT (LBS)	UNDER I-BEAM TO GROUND	I-BEAM OL	USABLE WIDTH	I-BEAM H x W	WT (LBS)	STOCK #	EACH
1000	6'6" to 9'	8'	6'11"	5" x 3"	116	300272	\$
1000	8'6" to 11'	8'	6'11"	5" x 3"	135	300273	
1000	6'6" to 9'	10'	8'11"	6" x 3 3/8"	131	300274	
1000	8'6" to 11'	10'	8'11"	6" x 3 3/8"	150	300275	
1000	6'6" to 9'	12'	10'11"	8" x 4"	164	300276	
1000	8'6" to 11'	12'	10'11"	8" x 4"	183	300277	
1000	6'6" to 9'	15'	13'11"	8" x 4"	192	300278	
1000	8'6" to 11'	15'	13'11"	8" x 4"	211	300279	
2000	5'7" to 8'1"	8'	6'10"	6" x 3 3/8"	150	300280	
2000	7'7" to 10'1"	8'	6'10"	6" x 3 3/8"	157	300281	
2000	9'7" to 12'1"	8'	6'10"	6" x 3 3/8"	197	300282	
2000	5'7" to 8'1"	10'	8'10"	8" x 4"	180	300283	
2000	7'7" to 10'1"	10'	8'10"	8" x 4"	187	300284	
2000	9'7" to 12'1"	10'	8'10"	8" x 4"	227	300285	
2000	5'7" to 8'1"	12'	10'10"	8" x 4"	192	300286	
2000	7'7" to 10'1"	12'	10'10"	8" x 4"	199	300287	
2000	9'7" to 12'1"	12'	10'10"	8" x 4"	239	300288	
2000	5'7" to 8'1"	15'	13'10"	10" x 4 5/8"	248	300289	
2000	7'7" to 10'1"	15'	13'10"	10" x 4 5/8"	255	300290	
2000	9'7" to 12'1"	15'	13'10"	10" x 4 5/8"	295	300291	
2000	5'10" to 8'4"	18'	16'9"	12" x 5"	389	300292	
2000	7'10" to 10'4"	18'	16'9"	12" x 5"	401	300293	
2000	9'10" to 12'4"	18'	16'9"	12" x 5"	441	300294	
2000	5'10" to 8'4"	20'	18'9"	12" x 5"	423	300295	
2000	7'10" to 10'4"	20'	18'9"	12" x 5"	435	300296	
2000	9'10" to 12'4"	20'	18'9"	12" x 5"	475	300297	

### Accessories for Aluminum Gantry Cranes

MAX WEIGHT (LBS)	STOCK #	EACH
<b>PNEUMATIC TIRES WITHOUT BRAKES</b>		
1000	300236	\$
2000	300237	
4000	300238	
6000	300239	
<b>PNEUMATIC TIRES WITH BRAKES</b>		
1000	300240	\$
2000	300241	
4000	300242	
6000	300243	



MAX WEIGHT (LBS)	STOCK #	EACH
<b>REPL. 6" POLY CASTER WHEELS WITH BRAKES</b>		
2000	300634	\$
2000	300635	
<b>REPL. 8" POLY CASTER WHEELS WITH BRAKES</b>		
4000	300636	\$
6000	300637	
<b>ALUMINUM GANTRY CRANE HEIGHT EXTENSIONS, 2'</b>		
1000	300324	\$
2000	300325	
4000	300322	
5000	300323	





T-Series Gantry Crane  
300244

## T-Series Aluminum Gantry Cranes

- Three-way adjustable beams let you configure T-series cranes to your specific work area

Configure these crane to work area conditions like uneven floors; through doorways or aisles; and under mezzanines or other overhead obstacles. Spanloc™ design ensures I-beam positioning remains completely stable during span adjustments. Push/pull pins on the main legs adjust height in 6" intervals. The adjustable tread uses a cable assembly bolted inside the caster frame tubes to prevent overspreading. "A" frame design eliminates swaying common to other adjustable gantry designs.

Enhance your T-series crane with optional accessories. Handy cart kits transform disassembled cranes into a handcart for easy transport around jobsites. For additional space under the span, detachable height adjustment kits adjust crane's height from 6'2" to 9'6" in 6" increments.

Shipping: All cranes ship motor freight.



### T-Series Aluminum Gantry Cranes

MAX WEIGHT (LBS)	UNDER I-BEAM TO GROUND	I-BEAM OL	USABLE WIDTH	I-BEAM H x W	WT (LBS)	STOCK #	EACH
2000	6'2" to 9'6"	10'	5'2"	6" x 3 <sup>3</sup> / <sub>8</sub> "	808	300244	\$
2000	7'4" to 11'11"	10'	5'2"	8" x 4"	935	300245	
2000	9'7" to 14'9"	10'	5'1"	8" x 4"	1028	300246	
2000	11'5" to 17'10"	10'	5'	8" x 4"	1239	300247	
2000	14' to 21'10"	10'	5'	8" x 4"	1343	300248	
2000	5'10" to 9'1"	15'	10'4"	10" x 4 <sup>5</sup> / <sub>8</sub> "	865	300249	
2000	7'3" to 11'9"	15'	10'3"	10" x 4 <sup>5</sup> / <sub>8</sub> "	965	300250	
2000	9'5" to 14'7"	15'	10'2"	10" x 4 <sup>5</sup> / <sub>8</sub> "	1059	300251	
2000	11'3" to 17'9"	15'	10'1"	10" x 4 <sup>5</sup> / <sub>8</sub> "	1272	300252	
2000	13'6" to 20'6"	15'	10'1"	12" x 5"	1375	300253	
4000	5'10" to 9'1"	10'	5'7"	10" x 4 <sup>5</sup> / <sub>8</sub> "	885	300254	
4000	7'3" to 11'10"	10'	5'6"	10" x 4 <sup>5</sup> / <sub>8</sub> "	1112	300255	
4000	9'5" to 14'7"	10'	5'5"	10" x 4 <sup>5</sup> / <sub>8</sub> "	1234	300256	
4000	11'3" to 17'8"	10'	5'4"	10" x 4 <sup>5</sup> / <sub>8</sub> "	1449	300257	
4000	13'8" to 20'8"	10'	5'3"	10" x 4 <sup>5</sup> / <sub>8</sub> "	1662	300258	
4000	5'10" to 9'1"	15'	10'3"	12" x 5"	1008	300259	
4000	7'2" to 11'9"	15'	10'2"	12" x 5"	1133	300260	
4000	9'5" to 14'7"	15'	10'	12" x 5"	1244	300261	
4000	11'2" to 17'8"	15'	10'	12" x 5"	1354	300262	
4000	13'7" to 20'8"	15'	9'11"	12" x 5"	1792	300263	
6000	6' to 9'4"	10'	5'	10" x 4 <sup>5</sup> / <sub>8</sub> "	1284	300264	
6000	7'5" to 12'	10'	4'11"	10" x 4 <sup>5</sup> / <sub>8</sub> "	1484	300265	
6000	9'5" to 14'7"	10'	4'11"	12" x 5"	1617	300266	
6000	11'3" to 17'8"	10'	3'3"	12" x 5"	1842	300267	
6000	5'11" to 9'2"	15'	10'1"	12" x 5"	1418	300268	
6000	7'3" to 11'10"	15'	10'	12" x 5"	1615	300269	
6000	9'5" to 14'7"	15'	9'11"	12" x 5"	1778	300270	
6000	11'3" to 17'8"	15'	8'3"	12" x 5"	2050	300271	

### Accessories for T-Series Aluminum Gantry Cranes

DESCRIPTION	STOCK #	EACH
Handy Cart Kit for 1- and 2-Ton Cranes	300124	\$
Handy Cart Kit for 3- and 5-Ton Cranes	300125	
Detachable Height Adjustment Kit	300126	



Crane with Aluminum Flat Feet 64537

## Spanco® Industrial Tripod Cranes


- Easily lower pumps or equipment into confined spaces
- Adjustable legs for uneven ground
- Great for outdoor sites



Spanco Industrial Tripod Cranes are a heavy-lifting solution you can take virtually anywhere. Easily transported and operated by a single person, they make lifting heavy equipment into confined spaces, tanks, digesters and manholes easy. The tripod's free-swiveling eyebolt hangs plumb to protect the head from twists and strains, while also keeping the lifting device perfectly erect. The included lashing kit prevents legs from spreading while lifting.

Optional tripod feet improve grip in your specific jobsite. Choose aluminum flat feet for use on stable and solid surfaces. Steel mud feet are ideal for less stable and softer surfaces. Both are sold in sets of 3.

Note: These are strictly equipment tripod cranes and are not to be used for lifting, supporting or transporting personnel.



Shipping: All cranes ship motor freight.



### Tripod Cranes

MAX WEIGHT (LBS)	UNDER EYEBOLT TO GROUND	USABLE WIDTH	WT (LBS)	STOCK #	EACH
<b>ALUMINUM TRIPOD CRANE WITH ALUMINUM FLAT FEET</b>					
2000	5'2" to 8'7"	9'2"	60	64537	\$
2000	6'10" to 11'2"	11'9"	70	64539	
2000	8'7" to 13'9"	14'6"	140	64548	
4000	6'10" to 11'2"	11'9"	120	64657	
4000	8'7" to 13'9"	14'6"	140	64549	
<b>ALUMINUM TRIPOD CRANE WITH STEEL MUD FEET</b>					
2000	5'2" to 8'7"	9'2"	60	300119	\$
2000	6'10" to 11'2"	11'9"	70	300120	
2000	8'7" to 13'9"	14'6"	140	300121	
4000	6'10" to 11'2"	11'9"	120	300122	
4000	8'7" to 13'9"	14'6"	140	300123	

### Optional Tripod Feet

DESCRIPTION	STOCK #	EACH
Aluminum Flat Feet, Set of 3	64497	\$
Steel Mud Flat Feet, Set of 3	64498	