

Plastic Tube Fittings

• Rated for pressures up to 220 psi

Polypropylene fittings have good chemical resistance and are unaffected by weak acids and bases. Withstands continuous temperatures up to 215°F (101.7°C) with good resistance to organic solvents below 175°F (79.4°C). Do not use with oxidants, strong acids or in continuous sunlight. NSF listed.



Male Connectors

TUBE x NPT(M)	POLYPROPYLENE		PVDF	
	STOCK #	10/PK	STOCK #	10/PK
1/4" x 1/4"	85408	\$	85420	\$
1/4" x 3/8"	85409		85421	
3/8" x 1/4"	85410		85422	
3/8" x 3/8"	85411		85423	
3/8" x 1/2"	85412		85424	
1/2" x 1/4"	85413		85425	
1/2" x 3/8"	85414		85426	
1/2" x 1/2"	85415		85427	
5/8" x 3/8"	85416		85428*	
5/8" x 1/2"	85417		85429*	
3/4" x 1/2"	85418*		85430*	
3/4" x 3/4"	85419*		85431*	

* Sold in packs of 5.



Male Elbows

TUBE x NPT(M)	POLYPROPYLENE		PVDF	
	STOCK #	10/PK	STOCK #	10/PK
1/4" x 1/4"	85432	\$	85440	\$
1/4" x 3/8"	85433		85441	
3/8" x 1/4"	85434		85442	
3/8" x 3/8"	85435		85443	
1/2" x 1/4"	85436		85444	
1/2" x 3/8"	85437		85445	
1/2" x 1/2"	85438		85446	
5/8" x 1/2"	85439		85447*	

* Sold in packs of 5.



Male Branch Tees

TUBE x TUBE x NPT(M)	POLYPROPYLENE		PVDF	
	STOCK #	10/PK	STOCK #	10/PK
1/4" x 1/4" x 1/4"	85448	\$	85453	\$
3/8" x 3/8" x 1/4"	85449		85454	
3/8" x 3/8" x 3/8"	85450		85455	
1/2" x 1/2" x 3/8"	85451		85456	
1/2" x 1/2" x 1/2"	85452		85457	



Unions

TUBE x TUBE	POLYPROPYLENE		PVDF	
	STOCK #	10/PK	STOCK #	10/PK
1/4" x 1/4"	85458	\$	85467	\$
3/8" x 1/4"	85651		85468	
3/8" x 3/16"	79299		—	—
3/8" x 3/8"	85461		85469	
1/2" x 3/8"	85462		85470	
1/2" x 1/2"	85463		85471	
5/8" x 1/2"	85464		85472*	
5/8" x 5/8"	85465		85473*	
3/4" x 3/4"	85466*		85474*	

* Sold in packs of 5.



Union Tees

TUBE x TUBE x TUBE	POLYPROPYLENE		PVDF	
	STOCK #	10/PK	STOCK #	10/PK
1/4" x 1/4" x 1/4"	85475	\$	85479	\$
3/8" x 3/8" x 3/8"	85476		85480	
1/2" x 1/2" x 1/2"	85477		85481	
5/8" x 3/8" x 3/8"	85478		85482*	

* Sold in packs of 5.

PVDF fittings have outstanding chemical resistance for handling highly corrosive fluids, including strong acids, bases and chlorine. Temperature range of -80 to 275°F (-62 to 135°C), except in acids, where the maximum rating is 220°F (104.4°C). UV-resistant except in chlorine applications when fittings should be wrapped if exposed to continuous sunlight. FDA and NSF listed.



Bulkhead Unions

TUBE x TUBE	POLYPROPYLENE		PVDF	
	STOCK #	10/PK	STOCK #	10/PK
1/4" x 1/4"	85483	\$	85486	\$
3/8" x 3/8"	85484		85487	
1/2" x 1/2"	85485		85488	



Female Connectors

TUBE x NPT(F)	POLYPROPYLENE		PVDF	
	STOCK #	10/PK	STOCK #	10/PK
1/4" x 1/4"	85489	\$	85496	\$
3/8" x 1/4"	85490		85497	
3/8" x 3/8"	85491		85498	
3/8" x 1/2"	85492		85499	
1/2" x 3/8"	85493		85500	
1/2" x 1/2"	85494		85501	
3/8" x 1/2"	85495		85502*	

* Sold in packs of 5.



Female Elbows

TUBE x NPT(F)	POLYPROPYLENE		PVDF	
	STOCK #	10/PK	STOCK #	10/PK
1/4" x 1/4"	85503	\$	85509	\$
3/8" x 1/4"	85504		85510	
3/8" x 3/8"	85505		85511	
1/2" x 3/8"	85506		85512	
1/2" x 1/2"	85507		85513	
5/8" x 1/2"	85508		85514*	

* Sold in packs of 5.



Union Elbows

TUBE x TUBE	POLYPROPYLENE		PVDF	
	STOCK #	10/PK	STOCK #	10/PK
1/4" x 1/4"	85515	\$	85520	\$
3/8" x 3/8"	85516		85521	
1/2" x 1/2"	85517		85522	
5/8" x 3/8"	85518		85523*	
3/4" x 3/4"	85519*		85524*	

* Sold in packs of 5.



Male Run Tees

TUBE x TUBE x NPT(M)	POLYPROPYLENE		PVDF	
	STOCK #	10/PK	STOCK #	10/PK
1/4" x 1/4" x 1/4"	85525	\$	85530	\$
3/8" x 3/8" x 1/4"	85526		85531	
3/8" x 3/8" x 3/8"	85527		85532	
1/2" x 1/2" x 3/8"	85528		85533	
1/2" x 1/2" x 1/2"	85529		85534	

We also RECOMMEND...

Bulkhead Fittings



The suction bulkhead fitting permits drawing of chemical from the side of the tank, rather than the top. Install by drilling a hole through the solution tank sidewall. Required EPDM seals are included.

DESCRIPTION	STOCK #	EACH
Bulkhead, 3/8" OD Tubing	29076	\$
Bulkhead, 1/2" OD Tubing	29052	
Bulkhead, 1/2" NPT(F)	29051	
Tube Adapter, 3/8" x 1/4", Pack of 10	85651	