

# CHEMICAL FEED & DISINFECTION Tubing & Fittings

## PFA Compression Fittings

- Ideal for corrosive environments
- Leak-tight connection; no tools required
- Rated to 125 psi

PFA fluoropolymer fittings are ideal for use in severely corrosive environments—they stand up to harsh chemical applications. These easy-to-use fittings provide a leak-tight connection without requiring any tools. Just insert your tubing into the fitting assembly and tighten the nut.

### Male Connectors

TUBE OD x NPT(M)	STOCK #	EACH
1/4" x 1/4"	62789	\$
1/4" x 3/8"	62790	
1/4" x 1/2"	62791	
3/8" x 1/4"	62792	
3/8" x 3/8"	62793	
3/8" x 1/2"	62794	
1/2" x 1/4"	62795	
1/2" x 3/8"	62796	
1/2" x 1/2"	62797	



Male Connector

### Female Connectors

TUBE OD x NPT(F)	STOCK #	EACH
1/4" x 1/4"	62798	\$
1/4" x 3/8"	62799	
1/4" x 1/2"	62800	
3/8" x 1/4"	62801	
3/8" x 3/8"	62802	
3/8" x 1/2"	62803	
1/2" x 1/4"	62804	
1/2" x 3/8"	62805	
1/2" x 1/2"	62806	



Female Connector

### Union Connectors

TUBE OD x TUBE OD	STOCK #	EACH
1/4" x 1/4"	62807	\$
3/8" x 3/8"	62808	
1/2" x 1/2"	62809	
3/8" x 1/4"	62810	
1/2" x 1/4"	62811	
1/2" x 3/8"	62812	



Union Connector

### Male Elbows


TUBE OD x NPT(M)	STOCK #	EACH
1/4" x 1/4"	62813	\$
1/4" x 3/8"	62814	
1/4" x 1/2"	62815	
3/8" x 1/4"	62816	
3/8" x 3/8"	62817	
3/8" x 1/2"	62818	
1/2" x 1/4"	62819	
1/2" x 3/8"	62820	
1/2" x 1/2"	62821	



Male Elbow

### Female Elbows

TUBE OD x NPT(F)	STOCK #	EACH
3/8" x 1/4"	62823	\$
3/8" x 3/8"	62824	
3/8" x 1/2"	62825	
1/2" x 1/2"	62826	



Female Elbow

### Union Elbows

TUBE OD x TUBE OD	STOCK #	EACH
1/4" x 1/4"	62827	\$
3/8" x 3/8"	62828	
1/2" x 1/2"	62829	
3/8" x 1/4"	62830	
1/2" x 1/4"	62831	



Union Elbow

### Male Branch Tees

TUBE OD x TUBE OD x NPT(M)	STOCK #	EACH
1/4" x 1/4" x 1/4"	62833	\$
3/8" x 3/8" x 1/2"	62836	
1/2" x 1/2" x 1/4"	62837	
1/2" x 1/2" x 1/2"	62839	



Male Branch Tee

### Tee Unions

TUBE OD x TUBE OD x TUBE OD	STOCK #	EACH
1/4" x 1/4" x 1/4"	62840	\$
3/8" x 3/8" x 3/8"	62841	
1/2" x 1/2" x 1/2"	62842	



Tee Union

## Polypropylene Shutoff Valves

- NSF 51 and 61 approved
- Pressures to 150 psi

These valves feature polypropylene construction with EPDM O-rings. Choose from 1/4" and 3/8" sizes. Suitable for potable water applications. Pressure rated to 150 psi at 70°F and 60 psi at 140°F.

**Note:** Not for use with sodium hypochlorite. Contact USABlueBook for questions about material compatibility.



### Male Connectors

TUBE OD x NPT(M)	STOCK #	PK OF 10
1/4" x 1/4"	85625	\$
3/8" x 3/8"	85626	



### Union Connectors

TUBE OD x TUBE OD	STOCK #	PK OF 10
1/4" x 1/4"	85627	\$
3/8" x 3/8"	85628	



### Female Connectors

TUBE OD x NPT(F)	STOCK #	PK OF 10
1/4" x 1/4"	85629	\$
3/8" x 1/4"	85630	