

Polypropylene Push-to-Connect Fittings

- NSF 51 and 61 approved
- Pressures to 150 psi

These high-quality fittings are fast and easy to use. They're made from white polypropylene and come with a food-grade EPDM O-ring to seal. Use for a variety of applications. Pressure rated to 150 psi at 70°F and 60 psi at 140°F.

Note: Not for use with sodium hypochlorite. Contact USABlueBook for questions about material compatibility.



Male Connectors

TUBE x NPT(M)	STOCK #	PACK OF 10
1/4" x 1/4"	85609	\$
1/4" x 3/8"	85610	
3/8" x 1/4"	85611	
3/8" x 3/8"	85612	
3/8" x 1/2"	85613	
1/2" x 3/8"	85614	
1/2" x 1/2"	85615	



Union Tees

TUBE x TUBE	STOCK #	PACK OF 10
1/4" x 1/4"	85616	\$
3/8" x 3/8"	85617	
1/2" x 1/2"	85618	



Union Elbows

TUBE x TUBE	STOCK #	PACK OF 10
1/4" x 1/4"	85619	\$
3/8" x 3/8"	85620	
1/2" x 1/2"	85621	



Union Connectors

TUBE x TUBE	STOCK #	PACK OF 10
1/4" x 1/4"	85622	\$
3/8" x 3/8"	85623	
1/2" x 1/2"	85624	



PVC Hose Barb Fittings

PVC construction allows use with many chemicals

Couplings

HOSE BARB x HOSE BARB	QTY/PK	STOCK #	PACK
1/2" x 1/2"	5	42036	\$
3/4" x 3/4"	5	42037	
1" x 1"	5	42038	
1 1/4" x 1 1/4"	1	42039	
1 1/2" x 1 1/2"	1	42040	
2" x 2"	1	42041	



Female Adapters

FEMALE NPT x HOSE BARB	QTY/PK	STOCK #	PACK
1/2" x 1/2"	5	42063	\$
3/4" x 3/4"	5	42064	
1" x 1"	5	42065	
1 1/4" x 1 1/4"	1	42066	
1 1/2" x 1 1/2"	1	42067	
2" x 2"	1	42068	



Male Adapters

MALE NPT x HOSE BARB	QTY/PK	STOCK #	PACK
1/2" x 1/2"	5	42069	\$
3/4" x 3/4"	5	42070	
1" x 1"	5	42071	
1 1/4" x 1 1/4"	1	42072	
1 1/2" x 1 1/2"	1	42073	
2" x 2"	1	42074	



Male Reducing Adapters

MALE NPT x HOSE BARB	QTY/PK	STOCK #	PACK
1/2" x 3/4"	5	42075	\$
3/4" x 1/2"	5	42076	
3/4" x 1"	5	42077	
1" x 3/4"	5	42078	



To choose correct hose barb size, measure the inner diameter of your tubing.

operator notes

PVDF Push-to-Connect Fittings

- Strong resistance to wide range of chemicals
- Working pressure to 300 psi at 73°F

These lightweight push-to-connect fittings let you connect plastic tubing without using tools. Their deep tube seat and all-plastic collet design provide compatibility with polyethylene, fluoropolymer and other plastic tubing.

Fittings feature PVDF and Viton® construction, making them ideal for use with oxidizers like sodium hypochlorite. All components are made from FDA-compliant materials, and have a temperature rating of 0 to 275°F.

Male Connectors

TUBE x NPT(M)	STOCK #	EACH
1/4" x 1/4"	67086	\$
1/4" x 3/8"	67087	
3/8" x 1/4"	67088	
3/8" x 3/8"	67089	
3/8" x 1/2"	67090	



Union Tees

TUBE x TUBE x TUBE	STOCK #	EACH
1/4" x 1/4" x 1/4"	67091	\$
3/8" x 3/8" x 3/8"	67092	



Union Elbows

TUBE x TUBE	STOCK #	EACH
1/4" x 1/4"	67093	\$
3/8" x 1/4"	67094	
3/8" x 3/8"	67095	



Union Connectors

TUBE x TUBE	STOCK #	EACH
1/4" x 1/4"	67096	\$
3/8" x 1/4"	67097	
3/8" x 3/8"	67098	

Female Connectors

TUBE x NPT(F)	STOCK #	EACH
1/4" x 1/4"	67099	\$
3/8" x 1/4"	67100	
3/8" x 3/8"	67101	



Stem Adapters

NPT(M) x STEM	STOCK #	EACH
1/4" x 1/4"	67102	\$
3/8" x 1/4"	67103	
3/8" x 3/8"	67104	



Male Elbows

TUBE x NPT(M)	STOCK #	EACH
1/4" x 1/4"	67109	\$
1/4" x 3/8"	67110	
3/8" x 1/4"	67111	
3/8" x 3/8"	67112	

