

VALVES Ball



Apollo® 76F Domestic SS Ball Valves

- Full port design prevents pressure fluctuations
- Fully manufactured and assembled in the U.S.A.

These stainless steel valves feature an adjustable packing gland and a blowout-proof stem. Their 316 SS balls, stems and nuts ensure optimal corrosion resistance. Available in socket-welded, solder-joint, grooved and flared-end designs as special order; contact USABlueBook for details.

Valve construction:	316 SS
Seat:	RPTFE
Max psi rating:	1000 psi
Application:	on/off service
Connections:	NPT(F)
Certifications:	NACE MR-01-75

MFR #	SIZE	STOCK #	EACH	MFR #	SIZE	STOCK #	EACH
76F-101-01	1/4"	40532	\$	76F-105-01	1"	40536	\$
76F-102-01	3/8"	40533		76F-106-01	1 1/4"	40537	
76F-103-01	1/2"	40534		76F-107-01	1 1/2"	40538	
76F-104-01	3/4"	40535		76F-108-01	2"	40539	



Superior corrosion resistance

Stainless Steel Full Port Ball Valves

- Choose from 304 or 316 stainless steel

These ball valves feature stainless steel bodies, stems and balls, plus RTFE seats for superior corrosion resistance in a wide variety of applications. Choose from 304 or 316 SS construction. 316 SS valves include a lockable handle.

	316 SS Valves	304 SS Valves
Valve construction (body, ball and stem):	316 stainless steel	304 stainless steel
Seat:	RTFE	RTFE
Max psi rating:	1000 psi	800 psi
Application:	on/off service	on/off service
Connections:	NPT(F)	NPT(F)
Locking handle:	yes	no

PIPE SIZE NPT(F)	316 SS VALVES		304 SS VALVES	
	STOCK #	EACH	STOCK #	EACH
1/4"	16957	\$	57368	\$
3/8"	16959		57369	
1/2"	16960		57370	
3/4"	16961		57371	
1"	16962		57372	
1 1/4"	16963		57373	
1 1/2"	16964		57374	
2"	16965		57375	
2 1/2"	16967		—	—
3"	16968		—	—

Choose from stainless or carbon steel



Three-Piece Ball Valves



- Full port with lockable handle

These full port ball valves feature a blowout-proof stem and come standard with a lockable handle. Their three-piece design means you can easily remove the center part of the valve for cleaning or repair without removing the pipes from the valve body. Valves feature a rugged 316 stainless steel ball and a built-in actuator mounting pad.

Valve construction:	stainless or carbon steel
Seat:	PTFE
Ball:	316 stainless steel
Max psi rating:	1000 WOG
Connections:	NPT(F)
Applications:	on/off service

SIZE	STAINLESS STEEL		CARBON STEEL	
	STOCK #	EACH	STOCK #	EACH
1/4"	62932	\$	62940	\$
3/8"	62933		62941	
1/2"	62934		62942	
3/4"	62935		62943	
1"	62936		62944	
1 1/4"	62937		62945	
1 1/2"	62938		62946	
2"	62939		62947	

We also RECOMMEND...



Master Lock® Ball Valve Lockouts

- Effective lockout for virtually any ball valve

Seal Tight™ handle-on ball valve lockouts clamp tightly onto handle stops to prevent handle movement. Use on 1/4 to 4" valves. Lightweight adjustable ball valve lockouts feature durable thermoplastic construction that is chemically resistant and performs well in extreme environments. Use on 1/2 to 2" valves. See page 1539 for more information. Order padlock separately on page 1538.

DESCRIPTION	MATERIAL	STOCK #	EACH
Handle-On Ball Valve Lockout	Aluminum/Steel	27594	\$
Adjustable Ball Valve Lockout	Thermoplastic	27595	