



301478



301470



92828



Technocheck Blower Check Valves

- Silicone seals rated at 500°F
- Stable operation under a wide range of flow rates

Techno blower check valves offer low pressure loss in a low-maintenance design. They feature a stationary hinge post and hinge clamp to reduce wear to hinges, pins, valve seats and springs.

The valve plate features complete metal-to-metal support and minimal travel from fully open to fully closed, which allows for quick closure without slamming. A unique flexible elastomer seal provides the final closure around the valve bore to deliver continuous strength and durability. Choose from several valve materials; all feature an aluminum disc plate/internals.

Note: For maximum life, check valves should be installed with at least six pipe diameters of straight unrestricted piping upstream and downstream of the valve. Repair Kits are available by special order; contact us for details.

Valve construction:	aluminum, cast iron or carbon steel
Seals:	silicone
Max psi rating:	50 psi (threaded and flanged); 125 psi (wafer)
Operating temp range:	-100 to 500°F
Connections:	threaded (NPT), wafer or flanged

PIPE SIZE	LAY LENGTH	STOCK #	EACH
ALUMINUM BODY/SILICONE SEALS, THREADED			
1"	3 1/2"	301470	\$
1 1/4"	3 1/2"	301471	
1 1/2"	4"	301472	
2"	4"	301473	
3"	5 1/2"	301474	
4"	6"	301475	
5"	7"	301476	
6"	8"	301477	
CAST IRON BODY/SILICONE SEALS, WAFER			
3"	1 7/8"	301478	\$
4"	2 3/8"	301479	
5"	2 7/8"	301480	
6"	3 3/8"	301481	
8"	4 3/8"	301482	
CAST IRON BODY/SILICONE SEALS, FLANGED			
4"	5 1/2"	92828	\$
5"	6"	92829	
6"	7"	92830	
8"	9"	92831	
10"	11"	92832	
12"	13"	92833	

Spring-Loaded Pressure Relief Valves

These valves are pre-set at the factory for a working pressure of 5 psi. You can easily adjust the valve to increase the pressure, depending on the actual pressure condition of the air manifold. Pressure range is 0 to 10 psi.

PIPE SIZE	STOCK #	EACH
1"	63728	\$
1 1/2"	63732	
2"	63730	
2 1/2"	63733	
3"	63729	
4"	63731	



Republic Spring-Loaded Pressure Relief Valves

- Preset at 5 psi
- Durable nickel-plated steel construction

Protect your blowers from overheating with these high-quality pressure relief valves. If a valve is shut while the blower is running, overheating can occur when there is an obstruction in the line or the water level is too high for the application. These valves are spring-loaded to prevent that from happening. Valves are preset to 5 psi and are user adjustable. Valves can also be factory preset to another psi of your choice. Contact us for details.

PIPE SIZE	STOCK #	EACH	PIPE SIZE	STOCK #	EACH
1"	37401	\$	2 1/2"	37405	\$
1 1/4"	37402		3"	37406	
1 1/2"	37403		4"	37407	
2"	37404				





We offer a wide variety of **Valves** from trusted manufacturers. See pages 1802-1875 for our full selection.



Watts Water Technologies, Inc.



