

Grässlin Hour Meters

- Trusted meters featured in many popular control panels
- Non-resettable 7-digit display

These hour meters feature the unmistakable look of Grässlin; white numerals on a black background with yellow tenth and hundredth numerals. **UWZ series meters** are for indoor use; multiple mounting options available. In addition to their yellow numerals, UWZ meters feature an orange dial that provides running indication. **FWZ series meters** can be used virtually anywhere thanks to their IP54 rating* (requires optional gasket; sold separately). All meters are 120 VAC. Alternate voltages available as special order. Contact USABlueBook for more information.



57514



57519



57520



57517

MFR #	MOUNTING	DIMENSIONS	STOCK #	EACH
UWZ SERIES HOUR METERS				
UWZ48-120U	Surface Mount	1.89"W x 1.89"H Bezel	57514	\$
UWZ48E-120U	Flush Mount w/ Bracket	1.79"W x 1.79"H Panel Opening	57516	
UWZ48V-120U	DIN Rail Mount	1.89"W x 1.89"H Bezel	57515	
FWZ SERIES HOUR METERS*				
FWZ53-120U	Flush Mount, Rectangular	1.5"W x 1"H Panel Opening	57519	\$
FWZ55-120U	Flush Mount, Rectangular	2.06"W x 1.08"H Panel Opening	57520	
FWZ72-120U	Flush Mount, Round	1.75"Dia Round Panel Opening	57517	
G-55U	IP54 Gasket for FWZ53 and FWZ55 Meters		57521	
G-72U	IP54 Gasket for FWZ72 Meters		57518	

*Gasket is required for IP54 rating; sold separately.



Clear dust cover protects the timer; solid dust cover protects the terminals.



Optional Outdoor Enclosure 57504

Electronic Timers with Battery Backup

- 24-hour, 7-day programming
- Up to 10 ON and 10 OFF events per day

This timer offers several features not offered by other brands. If you lose 120 VAC power, an internal battery keeps time, as well as your programmed schedule. The SPDT relay is rated at 16A @277 VAC, 1/2 hp @120 VAC, 1 hp @240 VAC, and 1000 watt tungsten @120/240 VAC.

Timer can be programmed to the minute and offers a manual override for on/off until the next scheduled event, when it resets itself to the program. One channel control offers 24-hour, 7-day programming with 10 ON/10 OFF setpoints and 3 block programs for different weekday schedules. LCD display shows time in AM/PM and provides output status indication.

This compact timer measures only 2.8"W x 4"H x 2"D, including base with screw terminals, so it fits inside of existing panel boxes. Use the optional NEMA 3R outdoor enclosure to mount the timer as a free standing unit. Enclosure measures 6 1/2"W x 10"H x 3 3/4"D and is lockable.

DESCRIPTION	STOCK #	EACH
Timer with Base	57503	\$
Optional NEMA 3R Outdoor Enclosure	57504	



Intermatic® Plug-In Timers

- Simple, economical on/off control

Use Intermatic's DT620 digital plug-in timer to turn lights and equipment on and off. Dawn/dusk setting adjusts automatically to sunrise/sunset times. Unit features two 120-VAC grounded receptacles. Rated up to 15 total amps.

MFR #	DESCRIPTION	STOCK #	EACH
DT620	Digital Plug-In Timer	57501	\$

