



## Asahi/America® Transparent PVC True Union Y-Strainers

- Transparent strainer body
- True Union design for quick and easy removal



These strainers feature a transparent PVC body, so you can easily see how much debris has been collected without taking off the end. True union design lets you remove and install the strainer body without disturbing any piping or threaded ends.

Each strainer is supplied with a PVC 20-mesh screen, EPDM O-rings and a set of socket and threaded ends. 30-mesh and 40-mesh replacement screens are available separately below; no other screen mesh sizes are available. Temperature range is 32 to 122°F; 150 psi at ambient temperature.

| PIPE SIZE | Strainers |      | Replacement Screens (Mesh) |            |            |      |
|-----------|-----------|------|----------------------------|------------|------------|------|
|           | STOCK #   | EACH | 20 STOCK #                 | 30 STOCK # | 40 STOCK # | EACH |
| 1/2"      | 16983     | \$   | 16890                      | 16891      | 16892      | \$   |
| 3/4"      | 16985     |      | 16893                      | 16894      | 16895      |      |
| 1"        | 16987     |      | 16896                      | 16897      | 16898      |      |
| 1 1/4"    | 16989*    |      | 16902                      | 16900      | 16901      |      |
| 1 1/2"    | 16991     |      | 16902                      | 16903      | 16904      |      |
| 2"        | 16994     |      | 16905                      | 16906      | 16907      |      |
| 3" SOC    | 16996     |      | 16908                      | 16909      | 16910      |      |
| 3" THR    | 16998     |      | 16908                      | 16909      | 16910      |      |
| 4" SOC    | 17000     |      | 16911                      | 16912      | 16913      |      |
| 4" THR    | 17002     |      | 16911                      | 16912      | 16913      |      |

\* Comes with threaded ends only. For socket ends, order stock # 87493.



## Zurn® Wilkins Bronze Y-Strainers

- Flush strainer without removing the screen



Zurn Wilkins Model SXL strainers protect delicate equipment such as pressure regulators, meters and backflow preventers by filtering sediment that can cause premature failure. The Model SXL is rated 300 psi WOG and 150 psi steam. Flush strainer of small contaminants without removing the screen by removing the small threaded plug (included) in the bottom of the housing. For convenience, some operators replace the plug with a ball valve.

| PIPE SIZE | STRAINERS |      | REPLACEMENT SCREENS |      |
|-----------|-----------|------|---------------------|------|
|           | STOCK #   | EACH | STOCK #             | EACH |
| 1/2"      | 38521     | \$   | 86186               | \$   |
| 3/4"      | 38522     |      | 86187               |      |
| 1"        | 38523     |      | 86188               |      |
| 1 1/4"    | 38524     |      | 86189               |      |
| 1 1/2"    | 38525     |      | 86190               |      |
| 2"        | 38526     |      | 86191               |      |
| 2 1/2"    | 38527     |      | 86192               |      |
| 3"        | 38528     |      | 86193               |      |



## Hayward® PVC Y-Strainers

- PVC housings will not rust or corrode
- Heavy-duty hex cap for easy clean out
- Choose from opaque or transparent PVC housings



Protect piping system components from dirt and debris in the process media. Screens are ultrasonically welded for superior strength and have an open area at least 2X the cross section of the pipe size. All Y-strainers work equally well in vertical or horizontal applications. We stock units with 1/32" PVC and 80 mesh stainless steel strainer screens.

### Y-Strainers with 1/32" PVC Screen

| PIPE SIZE                                 | SOCKET  |      | THREADED |      | REPLACEMENT SCREENS |      |
|---|---------|------|----------|------|---------------------|------|
|   | STOCK # | EACH | STOCK #  | EACH | STOCK #             | EACH |
| <b>Y-STRAINERS W/ TRANSPARENT HOUSING</b> |         |      |          |      |                     |      |
| 1/2"                                      | 86963   | \$   | 86957    | \$   | 68315               | \$   |
| 3/4"                                      | 86964   |      | 86958    |      | 68316               |      |
| 1"  | 86965   |      | 86959    |      | 68317               |      |
| 1 1/4"                                    | 86966   |      | 86960    |      | 68318               |      |
| 1 1/2"                                    | 86967   |      | 86961    |      | 68318               |      |
| 2"  | 86968   |      | 86962    |      | 68320               |      |

### Y-STRAINERS W/ OPAQUE HOUSING

|        |       |    |       |    |       |    |
|--------|-------|----|-------|----|-------|----|
| 1/2"   | 68290 | \$ | 68300 | \$ | 68315 | \$ |
| 3/4"   | 68291 |    | 68301 |    | 68316 |    |
| 1"     | 68292 |    | 68302 |    | 68317 |    |
| 1 1/4" | 68293 |    | 68303 |    | 68318 |    |
| 1 1/2" | 68294 |    | 68304 |    | 68318 |    |
| 2"     | 68295 |    | 68305 |    | 68320 |    |
| 2 1/2" | 68296 |    | 68306 |    | 68321 |    |
| 3"     | 68297 |    | 68307 |    | 68321 |    |
| 4"     | 68298 |    | 68308 |    | 68323 |    |
| 4" FLG | 68299 |    | —     | —  | 68323 |    |

### Y-Strainers with 80-Mesh Stainless Steel Screen

| PIPE SIZE                            | SOCKET  |      | THREADED |      | REPLACEMENT SCREENS |      |
|--------------------------------------|---------|------|----------|------|---------------------|------|
|                                      | STOCK # | EACH | STOCK #  | EACH | STOCK #             | EACH |
| <b>Y-STRAINERS W/ OPAQUE HOUSING</b> |         |      |          |      |                     |      |
| 1/2"                                 | 78351   | \$   | 78345    | \$   | 78462               | \$   |
| 3/4"                                 | 78363   |      | 78357    |      | 78472               |      |
| 1"                                   | 78375   |      | 78369    |      | 78483               |      |
| 1 1/4"                               | 78387   |      | 78381    |      | 78511               |      |
| 1 1/2"                               | 78399   |      | 78393    |      | 78511               |      |
| 2"                                   | 78411   |      | 78405    |      | 78526               |      |
| 2 1/2"                               | 78423   |      | 78417    |      | —                   | —    |
| 3"                                   | 78435   |      | 78429    |      | 78557               |      |
| 4"                                   | 78447   |      | 78441    |      | 78573               |      |
| 4" FLG                               | 78453   |      | —        | —    | 78573               |      |

### STAINLESS STEEL MESH SIZES

| Mesh Size | Inches  |
|-----------|---------|
| 325       | 0.0016" |
| 200       | 0.0029" |
| 80        | 0.0070" |
| 60        | 0.0092" |
| 40        | 0.0150" |
| 1/32"     | 0.0313" |
| 3/64"     | 0.0469" |
| 1/16"     | 0.0625" |
| 5/64"     | 0.0781" |
| 1/8"      | 0.1250" |
| 3/16"     | 0.1875" |
| 1/4"      | 0.2500" |
| 3/8"      | 0.3750" |
| 1/2"      | 0.5000" |

operator notes

### Don't See the Mesh Size You Need?

Models with stainless steel strainers are also available in a variety of other mesh sizes. Use this table for available mesh sizes. Call for more information.

Units with PVC strainers are only available with 1/32" mesh.