

## Single-Cartridge Filter Housings

These filter housings are manufactured from the highest quality FDA-grade materials. Use them with the filter cartridges sold separately on pages 380-383. Order mounting brackets, filter sump wrenches and replacement O-rings separately.

**USA BlueBook** BRAND PRODUCTS

**YOUR BEST VALUE!**

### USA BlueBook Single-Cartridge Filter Housings

- Only one cartridge to change or clean
- Flow rates from 10 to 30 gpm
- Withstand high pressures up to 250 psi and temperatures up to 250°F

These low-cost, high-quality single cartridge filter housings are designed for industrial and commercial filtration applications. They are available in cast iron/steel, 304L stainless steel and 316L stainless steel heads and sumps for a variety of applications.

Housings feature automatic centering of cartridges on the bottom seal plate. Centering springs align cartridge ends with each other at the filter head. A standard drain petcock lets you drain your fluid for easy cleaning.



MAX FLOW (GPM)*	INLET NPT(F)	IRON/STEEL HEAD AND SUMP STOCK #	EACH	304L SS HEAD AND SUMP STOCK #	EACH	316L SS HEAD AND SUMP STOCK #	EACH
<b>SINGLE CARTRIDGE FILTERS, 2 1/2" OD x 10" L</b>							
10	1/2"	35382	\$	35391	\$	35400	\$
10	3/4"	35383		35392		35401	
10	1"	35384		35393		35402	
<b>SINGLE CARTRIDGE FILTERS, 2 1/2" OD x 20" L</b>							
20	1/2"	35385	\$	35394	\$	35403	\$
20	3/4"	35386		35395		35404	
20	1"	35387		35396		35405	
<b>SINGLE CARTRIDGE FILTERS, 2 1/2" OD x 30" L</b>							
30	1/2"	35388	\$	35397	\$	35406	\$
30	3/4"	35389		35398		35407	
30	1"	35390		35399		35408	

\*Flow rates are guidelines only. Actual flow rates vary based on fluid, viscosity, cartridge type, micron rating and other factors.

## Heavy-Duty Water Filter Housings

- Designed for more demanding applications

Thick side walls and heavy-duty ribs provide greater strength. Pressure relief button prevents a mess when changing filters. Flow rates depend on the cartridge used with the housing.



SIZE (OD x L)	COLOR	INLET NPT(F)	STOCK #	EACH
2 1/2" x 10"	Blue	3/4"	68778	\$
2 1/2" x 20"	Blue	3/4"	68780	

### Accessories

DESCRIPTION	STOCK #	EACH
Mounting Bracket	68792	\$
Sump Wrench	68789	
Replacement EPM O-Ring	68797	

## High-Flow Water Filter Housings

- Best option for high flows

These housings are designed for 4 1/2" filters so they can handle higher flow rates. Flow rates depend on the cartridge used with the housing. Pressure relief button prevents a mess when changing filters.



SIZE (OD x L)	COLOR	INLET NPT(F)	STOCK #	EACH
4 1/2" x 10"	Blue	3/4"	68782	\$
4 1/2" x 10"	Blue	1"	68783	
4 1/2" x 10"	Blue	1 1/2"	68784	
4 1/2" x 20"	Blue	3/4"	68785	
4 1/2" x 20"	Blue	1"	68786	
4 1/2" x 20"	Blue	1 1/2"	68787	

### Accessories

DESCRIPTION	STOCK #	EACH
Mounting Bracket	68793	\$
Sump Wrench	68790	
Replacement EPM O-Ring	68798	



## Watts® Granulated Activated Carbon Cartridges

- Economically priced for low flow applications

Use to remove chlorine, tastes, odors and organic chemicals.

SIZE (OD x L)	FLOW (GPM)	CAPACITY (GAL)	STOCK #	EACH	QTY 10+
2 3/4" x 10"	1	2500	68799	\$	\$
2 3/4" x 20"	2	5000	68800		
4 1/2" x 9 3/4"	3	7500	68801		
4 1/2" x 20"	5	15,000	68802		



## Watts® Activated Carbon Block Cartridges

- High chlorine reduction and long life

These cartridges offer longer service life than granular filters. Use to remove chlorine, tastes, odors and organic chemicals. They feature two layers of pre-filtration (5- and 15-micron).

SIZE (OD x L)	FLOW (GPM)	CAPACITY (GAL)	STOCK #	EACH	QTY 10+
2 7/8" x 9 3/4"	1	20,000	68803	\$	\$
2 7/8" x 20"	2	45,000	68804		
4 1/2" x 9 3/4"	3	70,000	68805		
4 1/2" x 20"	7	150,000	68806		

