

GAUGES General-Purpose

Economy General-Purpose Pressure Gauges

Use these economical, reliable gauges for noncorrosive applications. Not suitable for use with potable water.

CAUTION: Do not use these gauges for chlorine applications.



WIKAI



WIKAI



USABlueBook
BRAND PRODUCTS

YOUR BEST VALUE!

A 2 1/2" WIKAI® Liquid-Filled Pressure Gauges

- Glycerin filled; perfect for use where pulsation or vibration exist
- Use with media that won't obstruct pressure systems or attack copper alloy parts
- Not for use with potable water

B 2 1/2" WIKAI® General-Purpose Pressure Gauges

- Features a corrosion-resistant case and dial

C 2 1/2" & 3 1/2" USABlueBook General-Purpose Pressure Gauges

- Suited for use with water, oil, air, gas or other noncorrosive media
- Black painted steel case with glass window

Accuracy:

A 2 1/2" WIKAI Liquid-Filled Gauges

±3/2/3%
Wetted materials: copper alloy
Case material: ABS plastic, plastic window
Process connection: 1/4" NPT(M), lower mount
Dial size: 2 1/2"
Pointer: aluminum
Fluid fill: glycerin

B 2 1/2" WIKAI Gauges

±3/2/3%
Wetted materials: copper alloy
Case material: black ABS, acrylic window
Process connection: 1/4" NPT(M), lower mount
Dial size: 2 1/2"
Pointer: aluminum
Fluid fill: none

C 2 1/2" & 3 1/2" USABlueBook Gauges

±3/2/3%
Wetted materials: brass
Case material: black painted steel, glass window
Process connection: 1/4" NPT(M), lower mount
Dial size: 2 1/2" or 3 1/2"
Pointer: aluminum
Fluid fill: none

A 2 1/2" WIKAI Liquid-Filled Gauges

RANGE	GRADS	STOCK #	EACH	QTY 6+
30" to 0" Hg VAC	0.5	23033	\$	\$
30" Hg to 30 psi	0.2/0.1	23035		
30" Hg to 60 psi	0.5/0.2	23036		
30" Hg to 100 psi	0.1/0.5	23037		
30" Hg to 160 psi	0.1/0.5	23038		
0 to 15 psi	0.5	23039		
0 to 30 psi	1	23040		
0 to 60 psi	2	23041		
0 to 100 psi	2	23042		
0 to 160 psi	5	23043		
0 to 200 psi	5	23044		

B 2 1/2" WIKAI General-Purpose Gauges

RANGE	GRADS	STOCK #	EACH	QTY 6+
30" to 0" Hg VAC	0.5	11991	\$	\$
30" Hg VAC to 15 psi	1/0.5	11992		
30" Hg VAC to 30 psi	2/1	11993		
0 to 10 psi	0.2	11994		
0 to 15 psi	0.2	11995		
0 to 30 psi	0.5	11996		
0 to 60 psi	1	11997		
0 to 100 psi	2	11998		
0 to 160 psi	2	11999		
0 to 200 psi	5	12000		
0 to 300 psi	5	12001		

C USABlueBook General-Purpose Gauges

RANGE	GRADS	STOCK #	EACH	QTY 6+
2 1/2" DIAMETER DIAL				
30" to 0" Hg VAC	0.5	84582	\$	\$
30" Hg VAC to 15 psi	0.5	84583		
30" Hg VAC to 30 psi	1	84584		
0 to 15 psi	0.2	84585		
0 to 30 psi	0.5	84586		
0 to 60 psi	1	84587		
0 to 100 psi	2	84588		
0 to 160 psi	2	84589		
0 to 200 psi	5	84590		
0 to 300 psi	5	84591		
3 1/2" DIAMETER DIAL				
30" to 0" Hg VAC	0.5	84592	\$	\$
30" Hg VAC to 30 psi	1	84593		
0 to 15 psi	0.2	84594		
0 to 30 psi	0.5	84595		
0 to 60 psi	1	84596		
0 to 100 psi	2	84597		
0 to 160 psi	2	84598		
0 to 200 psi	5	84599		
0 to 300 psi	5	84600		

It is best to operate a gauge at its midpoint for accuracy and to protect against overload.

operator notes