

GAUGES Digital

2 1/2" Dwyer® Digital Pressure Gauges

- Offers selectable digital engineering units for a very economical price
- Select between psi, in. Hg, ft wc, and in. wc
- ±1% accuracy

This economical digital gauge is the perfect choice for digitally monitoring the pressures of compatible liquids and gases. It features selectable engineering units, ±1% accuracy and digital push-button zero. Auto-shutoff after 20 minutes helps save battery life. Pressure limits 2X pressure range. CE listed.



Accuracy:	±1% full scale
Units:	psi, in. Hg, ft wc, in. wc
Process connection:	1/4" NPT(M)
Wetted materials:	316L SS
Case material:	ABS plastic
Power:	9 VDC battery (included shipped not connected)

RANGE	STOCK #	EACH	RANGE	STOCK #	EACH
30" Hg to 0 psi	11693	\$	0 to 100 psi	11697	\$
0 to 15 psi	11694		0 to 200 psi	11698	
0 to 30 psi	11695		0 to 300 psi	11699	
0 to 50 psi	11696				

2 1/2" SSI Digital Pressure Gauges

- High accuracy, ±0.25% of full scale
- NEMA 4X washdown rated
- Excellent price/performance ratio

This high-accuracy digital pressure gauge represents a significant cost savings over currently available gauges. It is compact and robust, making it well suited for a variety of applications where cost, size and performance are critical. Includes zero reset button and pressure unit selection button.



Accuracy:	±0.25% full scale, BFSL
Units:	psi, ft H ₂ O, bar
Process connection:	1/4" NPT(M), bottom
Wetted materials:	304L & 316L SS
Case material:	polycarbonate, NEMA 4X washdown-rated
Power:	9 VDC battery (included)

RANGE	STOCK #	EACH
0 to 50 psi	26934	\$
0 to 100 psi	26935	
0 to 200 psi	26936	
0 to 300 psi	26937	

3" SSI Digital Pressure Gauges with 4-20 mA Output

- Easily interface with monitoring and control systems
- High 0.25% full scale accuracy

These digital gauges are perfect for process control applications where continuous monitoring is needed. Use them to control outputs via the 4-20 mA signal and NPN limit switch. The backlit LCD displays pressure in your choice of psi, bar or MPa.

Program auto zero, peak hold and high/low pressure set points on the easy-to-use 3-button keypad. Gauges feature all laser-welded 304L/316L stainless steel wetted materials. Operate on external 8 to 30 VDC power supply.

Includes: digital gauge and mating connector with 6.5' cable. Power supply sold separately. **Note:** Gauges will not work without power supply.

Accuracy:	±0.25% full scale
Units:	psi, bar or MPa
Process connection:	1/4" NPT(M), bottom
Wetted materials:	304L & 316L SS
Case material:	polycarbonate, NEMA 4X washdown-rated
Outputs:	4-20 mA output signal with an NPN limit switch
Power:	8 to 30 VDC

RANGE	STOCK #	EACH
0 to 50 psi	88968	\$
0 to 100 psi	88969	
0 to 200 psi	88970	
0 to 300 psi	88971	

24-VDC Power Supply, 15W 74178

ASHCROFT®

3" Ashcroft® Digital Pressure Gauge/Transmitters

- Multi-functional digital gauge with 4-20 mA output
- Easy to read—large display
- Records min/max and peak pressure readings

Save money, time and space with this multi-functional gauge. Use it as a pressure transmitter or digital pressure gauge. Its easy-to-read menu-driven LCD screen makes configuration simple. Gauge features 0.25% full-scale accuracy and battery-powered local indicator. Records min/max and peak pressure readings. Loop-powered 4-20 mA output is adjustable within the pressure range of the gauge.

Accuracy:	±0.25% full scale
Units:	psi, in. H ₂ O, ft H ₂ O, mPa, mBar, kPa, kg/cm ² , bar, in Hg, mm Hg
Process connection:	1/4" NPT(M), bottom
Wetted materials:	17-4 PH SS sensor, 316 SS socket
Case material:	brushed SS
Power:	4-20 mA: 12 to 36 VDC, batteries: 2 AA alkaline, over 1000 hours

RANGE	STOCK #	EACH
0 to 30 psi	12922	\$
0 to 60 psi	12923	
0 to 100 psi	12924	
0 to 200 psi	12925	
0 to 300 psi	12926	