



Self-Leveling Floating Strainer

Bottom Guard Strainer

Floating Strainer Shown in Working Position



Kochek® Floating & Bottom Guard Strainers

- Strainers rise or fall to your level
- Floating strainer voted Best Water Handling Innovation by Fire Apparatus & Emergency Equipment Magazine

Kochek strainers feature tough powder-coated aluminum construction. Each strainer has a carrying handle for easy transport and placement. Choose floating or bottom guard strainers.

Self-leveling floating strainers work with you to stay level. These compact and lightweight units feature a self-leveling float and full-time swivel that keep the strainer in the right position. Vortex shield prevents whirlpooling around the strainer.

Bottom guard strainers let you pull water from the bottom of your tank, pond or anywhere else you need dewatering. Swiveling guard uses gravity to always place itself beneath the strainer, keeping mud and silt out of your strainer, and more importantly, out of your pump.

Note: Strainers are available in virtually any size and connection combination. Contact USABlueBook for more information.

| SIZE/CONNECTION | SELF-LEVELING FLOATING STRAINERS | | BOTTOM GUARD STRAINERS | |
|-----------------|----------------------------------|------|------------------------|------|
| | STOCK # | EACH | STOCK # | EACH |
| 2 1/2" NST | 52482 | \$ | 52489 | \$ |
| 2 1/2" Camlock | 52483 | | 52490 | |
| 3" Camlock | 52484 | | 52491 | |
| 4" NST | 52485 | | 52492 | |
| 4" Camlock | 52486 | | 52493 | |
| 6" NST | 52487 | | 52494 | |
| 6" Camlock | 52488 | | 52495 | |

Guard in position protecting the barrel strainer



Plastic Suction Strainers

Made from strong, rustproof high-density polyethylene, these strainers work in salt water, and with acids and chemicals. Completely rustproof.

| SIZE, NPT(F) | OPENINGS | STOCK # | EACH |
|--------------|-------------|---------|------|
| 1.5" | 0.25" x 1" | 44420 | \$ |
| 2.0" | 0.25" x 1" | 44422 | |
| 3.0" | 0.5" x 1.5" | 44424 | |



Steel Suction Strainers

Prevent large debris and solids from entering drainage pumps. Choose from round or square openings. Strainers with square openings are made from 14 gauge steel for extra strength. Strainers with round openings are made from 16 gauge steel. Both styles are cadmium plated to prevent corrosion. Threads are female NPSM.



| SIZE, NPSM(F) | OPENINGS | STOCK # | EACH |
|--|----------|---------|------|
| STRAINERS WITH ROUND OPENINGS, 16-GA STEEL | | | |
| 1 1/2" | 3/8" | 44396 | \$ |
| 2" | 3/8" | 44398 | |
| 2 1/2" | 3/8" | 44400 | |
| 3" | 3/8" | 44402 | |
| 4" | 3/8" | 44404 | |
| 6" | 1" | 44406 | |
| STRAINERS WITH SQUARE OPENINGS, 14-GA STEEL | | | |
| 1 1/2" | 1" | 44408 | \$ |
| 2" | 1 1/8" | 44410 | |
| 2 1/2" | 1 1/2" | 44412 | |
| 3" | 1 1/2" | 44414 | |
| 4" | 1 1/2" | 44416 | |
| 6" | 1 1/2" | 44418 | |

Skimmers

Ideal for sump areas or those times when you need to get as close to floor level as possible. Rugged all steel construction with either top or bottom holes depending on your requirement. The base diameters are at least four times that of hose ID, giving the unit a large stable base.



| SIZE, NPT(F) | OPENINGS | HEIGHT | DIA | BOTTOM HOLE | | TOP HOLE | |
|--------------|----------|--------|-------|-------------|------|----------|------|
| | | | | STOCK # | EACH | STOCK # | EACH |
| 1.5" | 0.375" | 2.5" | 9.5" | 44426 | \$ | 44432 | \$ |
| 2.0" | 0.375" | 2.5" | 9.5" | 44428 | | 44434 | |
| 3.0" | 0.375" | 2.5" | 12.0" | 44430 | | 44436 | |

Foot Valve/Strainers

Ductile iron foot valve/strainers make pump priming easy because water is held in the suction line between pump duty cycles. Designed for water service only. Repair kits include sealing components, weight and screw for valve.



| SIZE, NPT(F) | FOOT VALVE/STRAINERS | | REPAIR KITS | |
|--------------|----------------------|------|-------------|------|
| | STOCK # | EACH | STOCK # | EACH |
| 1 1/2" | 62324 | \$ | 62315 | \$ |
| 2" | 62325 | | 62317 | |
| 2 1/2" | 62326 | | 62313 | |
| 3" | 62327 | | 62319 | |
| 4" | 62328 | | 62321 | |
| 6" | 62329 | | 62323 | |
| 8" | 62330* | | 62331 | |

* Shipping: Ships motor freight.

Bronze Foot Valves & Strainers

- Spring-loaded poppet ensures positive sealing in vertical and horizontal mounting positions

This valve features bronze construction with a stainless steel screen. Rated 200 WOG.



| SIZE, NPT | OVERALL LENGTH | STOCK # | EACH |
|-----------|----------------|---------|------|
| 3/4" | 3 7/8" | 54806 | \$ |
| 1" | 4 5/8" | 54807 | |
| 1 1/4" | 5" | 54808 | |
| 1 1/2" | 6" | 54809 | |
| 2" | 7 5/16" | 54810 | |