

USA BlueBook BRAND PRODUCTS

YOUR BEST VALUE!

Lightweight aluminum construction



USA BlueBook 2 1/2" Flow Testing Diffusers

- 360° orientation to direct discharge
- Quick disconnect fittings for gauges

This 2 1/2" flow testing diffuser with pitot assembly makes flow testing and hydrant flushing quick and easy, while keeping you and your surroundings dry. The diffuser rotates 360° so you can direct the water discharge to a safe, convenient location. Built-in baffle reduces the pressure of the spray.

The pitot assembly consists of a 3-way valve, snubber and pitot tube, all made from brass for corrosion resistance. The 4" sub-zero glycerin-filled gauge is designed for extreme conditions and use. The lightweight aluminum diffuser plus pitot assembly only weighs 7 lbs. Choose from 100 or 160 psi ranges.



Includes: diffuser, 4" glycerin-filled gauge, 1/4" snubber, 1/4" 3-way valve and 1/4" pitot tube. **Kits also include:** hard-shell carrying case.

DESCRIPTION	STOCK #	EACH
DIFFUSERS (DO NOT INCLUDE CARRYING CASE)		
USA BlueBook 2 1/2" Flow Tester Diffuser w/ 100 psi Gauge	53143	\$
USA BlueBook 2 1/2" Flow Tester Diffuser w/ 160 psi Gauge	53144	
DIFFUSER KITS (INCLUDE CARRYING CASE)		
USA BlueBook 2 1/2" Flow Testing Diffuser Kit w/ 100 psi Gauge	53145	\$
USA BlueBook 2 1/2" Flow Testing Diffuser Kit w/ 160 psi Gauge	53146	
REPLACEMENT ITEMS & ACCESSORIES		
4" Gauge, 100 psi/1680 gpm	53148	\$
4" Gauge, 160 psi/2120 gpm	53147	
1/4" Pitot Tube Only	53150	
1/4" Pitot Tube, Valve & Snubber Assembly	53149	
Hard-Shell Carrying Case	96756	

See page 1563 for

Hydrant Flushing Signs.



USA BlueBook BRAND PRODUCTS

YOUR BEST VALUE!



USA BlueBook Street "T" Style Hydrant Diffusers

NEW!

- Prevents washout in yards and driveways
- Lightweight, virtually indestructible PVC construction

Position our "T" hydrant diffuser in the street when flushing hydrants, and watch the flow run harmlessly to the gutter or sewer. Diffuser is constructed of heavy-duty 4" PVC pipe, so it will never rust or corrode. Built-in feet on the bottom and a handle on the top make it easy to place and remove. Features a 2 1/2" NST(F) aluminum swivel connection.

Note: This diffuser is not designed to be mounted directly on the hydrant. Use 10 or 15'L hose (sold separately below) to properly position in the street or gutter.

DESCRIPTION	STOCK #	EACH
PVC Hydrant Diffuser, 2 1/2" NST(F)	96740	\$
RUBBER-COVERED HYDRANT DIFFUSER HOSE		
Fire Hose, 2 1/2" x 10'L, M & F NST	22596	\$
Fire Hose, 2 1/2" x 15'L, M & F NST	22597	

Mars Thrust Busters

- Prevents side thrust to hydrants
- Field test water meters without securing the hoses

Use with field water meter testers to eliminate the thrust associated with loose hose lying on the ground. The thrust buster reduces the force of flowing water from fire hydrants or hose lines to control erosion and direct the flow pattern safely, protecting the operator and surrounding property.

Sch 40 steel construction with type 11 fusion nylon coating. NST bronze female swivel fire-hose fittings. Choose from straight outlet or 30° angle outlet.

Note: not a metering device

SIZE NST	OUTLET	STOCK #	EACH
2 1/2"	Straight	22480	\$
2 1/2"	30° Up Angle	22481	



Hydrant Diffusers

Light duty

Lightweight and easy to handle. 2" PVC body with ABS nut. 45° discharge will swivel 360°. Thousands sold. 100% guarantee.

DESCRIPTION	STOCK #	EACH
2 1/2" Diffuser	22532	\$

