

USA BlueBook BRAND PRODUCTS

YOUR BEST VALUE!

USA BlueBook Jumbo Pleated Filter Cartridges

- Choose from standard filters or those that conform to NSF/ANSI 61
- 100% polypropylene pleated material allows higher flow rates
- 5-micron filters and larger are cleanable and reusable

These filter cartridges deliver maximum throughput and particle retention at the lowest pressure drop. The center tube, end cap and polypropylene filter media are thermally bonded as one unit for optimal strength and a positive seal.

5 micron-sized filter cartridges and larger can be cleaned and reused when pressure reaches 12 to 15 psid. Replace cartridges when pressures reach 25 to 30 psid. Maximum temperature: 160°F.

For use with: jumbo filter housings; see page 374.

SIZE (OD x L)	MICRON	FLOW (GPM)	STOCK #	EACH	QTY 4+
FILTERS CERTIFIED TO NSF/ANSI 61 STANDARDS					
7 ³ / ₄ " x 9 ⁵ / ₈ "	0.35	40	86851	\$	\$
7 ³ / ₄ " x 9 ⁵ / ₈ "	1A	40	86852		
7 ³ / ₄ " x 9 ⁵ / ₈ "	1	40	86853		
7 ³ / ₄ " x 9 ⁵ / ₈ "	5	40	86854		
7 ³ / ₄ " x 9 ⁵ / ₈ "	10	40	86855		
7 ³ / ₄ " x 9 ⁵ / ₈ "	20	40	86856		
7 ³ / ₄ " x 9 ⁵ / ₈ "	50	40	86857		
7 ³ / ₄ " x 9 ⁵ / ₈ "	100	40	86858		
7 ³ / ₄ " x 19 ¹ / ₂ "	0.35	80	86859		
7 ³ / ₄ " x 19 ¹ / ₂ "	1A	80	86860		
7 ³ / ₄ " x 19 ¹ / ₂ "	1	80	86861		
7 ³ / ₄ " x 19 ¹ / ₂ "	5	80	86862		
7 ³ / ₄ " x 19 ¹ / ₂ "	10	80	86863		
7 ³ / ₄ " x 19 ¹ / ₂ "	20	80	86864		
7 ³ / ₄ " x 19 ¹ / ₂ "	50	80	86865		
7 ³ / ₄ " x 19 ¹ / ₂ "	100	80	86866		
7 ³ / ₄ " x 30 ³ / ₄ "	0.35	130	86867		
7 ³ / ₄ " x 30 ³ / ₄ "	1A	130	86868		
7 ³ / ₄ " x 30 ³ / ₄ "	1	130	86869		
7 ³ / ₄ " x 30 ³ / ₄ "	5	130	86870		
7 ³ / ₄ " x 30 ³ / ₄ "	10	130	86871		
7 ³ / ₄ " x 30 ³ / ₄ "	20	130	86872		
7 ³ / ₄ " x 30 ³ / ₄ "	50	130	86873		
7 ³ / ₄ " x 30 ³ / ₄ "	100	130	86874		
STANDARD FILTERS					
7 ³ / ₄ " x 9 ⁵ / ₈ "	0.35	40	86875	\$	\$
7 ³ / ₄ " x 9 ⁵ / ₈ "	1A	40	86876		
7 ³ / ₄ " x 9 ⁵ / ₈ "	1	40	86877		
7 ³ / ₄ " x 9 ⁵ / ₈ "	5	40	86878		
7 ³ / ₄ " x 9 ⁵ / ₈ "	10	40	86879		
7 ³ / ₄ " x 9 ⁵ / ₈ "	20	40	86880		
7 ³ / ₄ " x 9 ⁵ / ₈ "	50	40	86881		
7 ³ / ₄ " x 9 ⁵ / ₈ "	100	40	86882		
7 ³ / ₄ " x 19 ¹ / ₂ "	0.35	80	86883		
7 ³ / ₄ " x 19 ¹ / ₂ "	1A	80	86884		
7 ³ / ₄ " x 19 ¹ / ₂ "	1	80	86885		
7 ³ / ₄ " x 19 ¹ / ₂ "	5	80	86886		
7 ³ / ₄ " x 19 ¹ / ₂ "	10	80	86887		
7 ³ / ₄ " x 19 ¹ / ₂ "	20	80	86888		
7 ³ / ₄ " x 19 ¹ / ₂ "	50	80	86889		
7 ³ / ₄ " x 19 ¹ / ₂ "	100	80	86890		
7 ³ / ₄ " x 30 ³ / ₄ "	0.35	130	86891		
7 ³ / ₄ " x 30 ³ / ₄ "	1A	130	86892		
7 ³ / ₄ " x 30 ³ / ₄ "	1	130	86893		
7 ³ / ₄ " x 30 ³ / ₄ "	5	130	86894		
7 ³ / ₄ " x 30 ³ / ₄ "	10	130	86895		
7 ³ / ₄ " x 30 ³ / ₄ "	20	130	86896		
7 ³ / ₄ " x 30 ³ / ₄ "	50	130	86897		
7 ³ / ₄ " x 30 ³ / ₄ "	100	130	86898		

HydroScientific™ Pleated Jumbo Filter Cartridges

- Deliver high flow capability and longer filter runs

NEW!



These robust pleated jumbo cartridges meet and exceed operational requirements in high-flow applications. They are constructed from binder and surfactant-free, 100% polyester NSF/ANSI 61-approved material. High dirt holding capacity and increased particle removal increases time between filter changeouts or washes. Cartridges are cleanable and reusable (5 micron and larger).

SIZE (OD x L)	MICRON	FLOW (GPM)*	STOCK #	EACH
7 ³ / ₄ " x 9 ⁵ / ₈ "	0.22	35	90736	\$
7 ³ / ₄ " x 9 ⁵ / ₈ "	0.35	35	90737	
7 ³ / ₄ " x 9 ⁵ / ₈ "	1	35	90738	
7 ³ / ₄ " x 9 ⁵ / ₈ "	1A	35	90739	
7 ³ / ₄ " x 9 ⁵ / ₈ "	5	35	90740	
7 ³ / ₄ " x 9 ⁵ / ₈ "	10	35	90741	
7 ³ / ₄ " x 9 ⁵ / ₈ "	20	35	90742	
7 ³ / ₄ " x 9 ⁵ / ₈ "	50	35	90743	
7 ³ / ₄ " x 9 ⁵ / ₈ "	100	35	90744	
7 ³ / ₄ " x 9 ⁵ / ₈ "	150	35	90745	
7 ³ / ₄ " x 19 ¹ / ₂ "	0.22	70	90747	
7 ³ / ₄ " x 19 ¹ / ₂ "	0.35	70	90748	
7 ³ / ₄ " x 19 ¹ / ₂ "	1	70	90749	
7 ³ / ₄ " x 19 ¹ / ₂ "	1A	70	90750	
7 ³ / ₄ " x 19 ¹ / ₂ "	5	70	90751	
7 ³ / ₄ " x 19 ¹ / ₂ "	10	70	90752	
7 ³ / ₄ " x 19 ¹ / ₂ "	20	70	90753	
7 ³ / ₄ " x 19 ¹ / ₂ "	50	70	90754	
7 ³ / ₄ " x 19 ¹ / ₂ "	100	70	90755	
7 ³ / ₄ " x 19 ¹ / ₂ "	150	70	90756	
7 ³ / ₄ " x 30 ³ / ₄ "	0.22	105	90758	
7 ³ / ₄ " x 30 ³ / ₄ "	0.35	105	90759	
7 ³ / ₄ " x 30 ³ / ₄ "	1	105	90760	
7 ³ / ₄ " x 30 ³ / ₄ "	1A	105	90761	
7 ³ / ₄ " x 30 ³ / ₄ "	5	105	90762	
7 ³ / ₄ " x 30 ³ / ₄ "	10	105	90763	
7 ³ / ₄ " x 30 ³ / ₄ "	20	105	90764	
7 ³ / ₄ " x 30 ³ / ₄ "	50	105	90765	
7 ³ / ₄ " x 30 ³ / ₄ "	100	105	90766	
7 ³ / ₄ " x 30 ³ / ₄ "	150	105	90767	

* Recommended flow. Max flow: 9⁵/₈" = 50 gpm; 19¹/₂" = 100 gpm; 30³/₄" = 150 gpm



See pages 1261-1265 for our complete selection of **Turbidity Analyzers.**